

Xerox[®] VersaLink[®] C8000 Color Printer







High Capacity Feeder

Two Tray Module

Office Finisher (shown with optional booklet maker)

BR Booklet Maker Finisher

The VersaLink C8000 Color Printer is built on Xerox[®] ConnectKey[®] Technology. For more information, go to www.ConnectKey.com.

SYSTEM SPECIFICATIONS	VERSALINK C8000DT
One-Sided Speed¹ 8.5 x 11 in. / A4 8.5 x 11 in. / A4 SEF 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm / 12 x 18 in / SRA3 / 320 x 450 mm	Up to 45 ppm (pages per minute) long edge feed (LEF) Up to 32 ppm Up to 26 ppm Up to 22 ppm
Two-Sided Speed¹ 8.5 x 11 in. / A4 8.5 x 11 in. / A4 SEF 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm / 12 x 18 in / SRA3 / 320 x 450 mm	Up to 45 ppm LEF Up to 32 ppm Up to 17 ppm Up to 15 ppm
Monthly Duty Cycle ²	Up to 205,000 pages / month
Recommended Average Monthly Print Volume ³	Up to 20,000 pages per month
Hard Drive	320 GB HDD (Optional)
Processor	1.6 GHz Dual-Core
Memory	4 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform [®] , Xerox [®] App Gallery App, Xerox [®] Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan

DEVICE SPECIFICATIONS					
ELECTRICAL REQUIREMENTS	ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127V +/-10 Frequency: 50/60 Hz +/-3				
Europe and Other Geographies	Voltage: 220-240V +/- 10 Frequency: 50/60 Hz +/-3				
POWER CONSUMPTION					
Printing ⁴	For 110V: 2.30 kWh For 220V: 2.32 kWh				
Standby Mode ⁴	110V: 75.3 Watts or less 220V: 73.8 Watts or less				
Sleep Mode ⁴	0.67 watts or less				
OPERATING ENVIRONMENT					
Required Temperature Range (Storage)	Below 48° C, and in compliance with MN2-810.13				
Required Temperature Range (Operating)	50° to 83° F (10° to 28° C) Must be 28° C or below if humidity is at 85 %				
Required Relative Humidity	15% to 85% Must be 62.5% or below at 32° C				
Sound Power Levels	Printing: 6.63 B(A) or less Standby: 3.24 B(A) or less				
	Full System (including finisher) Printing: 7.56 B(A) Standby: 3.36 B(A)				
Sound Pressure Levels	Printing: 56.8 dB or less Standby: 15.4 dB or less				
	Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB				
Boot Time (from Off to UI Ready)	Less than 60 seconds				
Warm-up Time (from Sleep to UI Ready)	Less than 10 seconds (without HDD) Less than 16 seconds (with HDD)				
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH DEPTH HEIGHT WEIGHT				
VersaLink C8000/DT	24.4 in. / 620 mm	28.5 in. / 723 mm	31.9 in. / 809.3 mm	178 lb. / 80.8 kg	
Two Tray Module	26.3 in. / 668.5 mm	28.5 in. / 723 mm	10.3 in. / 261.2 mm	60.0 lb. / 27.2 kg	
Tandem Tray Module	26.3 in. / 668.5 mm	28.5 in. / 723 mm	10.3 in. / 261.2 mm	74.5 lb. / 33.8 kg	
High Capacity Feeder	15.3 in. / 389 mm	23.7 in. / 602.9 mm	15.0 in. / 380.01 mm	63.9 lb. / 29.0 kg	
Office Finisher	22 in. / 559.8 mm	21.7 in. / 552 mm	39.8 in. / 1012 mm	61.7 lb. / 28.0 Kg	
Booklet Maker Finisher	11.75 in. / 298.5 mm 23.5 in. / 597 mm 42.5 in. / 1080 mm 20.3 lb. / 9.2 Kg				
BR Booklet Maker Finisher	30.28 in. / 769.2 mm 28.5 in. / 723 mm 41.5 in. / 1055.1 mm 134.3 lb. / 60.9 Kg				

Xerox[®] VersaLink[®] C8000 Color Printer

DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink C8000/DT	32.8 in. / 833 mm	28.2 in. / 717 mm	33.4 in. / 852 mm	209.4 lb. / 95 kg
High Capacity Feeder	20.7 in. / 526 mm	29.8 in. / 756 mm	19.3 in. / 491 mm	74.3 lb. / 33.7 kg
Two Tray Module	32.7 in. / 830 mm	33.5 in. / 850 mm	15.75 in. / 400 mm	72.7 lb. / 33 kg
Tandem Tray Module	32.7 in. / 830 mm	33.5 in. / 850 mm	15.75 in. / 400 mm	86 lb. / 39 kg
Office Finisher	27.2 in. / 690 mm	40.2 in. / 1021 mm	25.7 in. / 654 mm	82 lb. / 37 kg
Booklet Maker Finisher	20 in. / 507 mm	30 in. / 761 mm	17.2 in. / 437 mm	31 lb. / 14 kg
BR Booklet Maker Finisher	30 in. / 764 mm	30.5 in. / 774 mm	47.4 in. / 1203 mm	169.7 lb. / 77 kg
Horizontal Transport for BR Booklet Maker Finisher	21 in. / 533 mm	23.1 in. / 589 mm	12.6 in. / 319 mm	14.3 lb. / 6.5 kg

CERTIFICATIONS

To view the latest list of certifications, go to **www.xerox.com/OfficeCertifications**.

PRINT	
First-Print-Out Time	As fast as 11 seconds color
	As fast as 11 seconds black and white
Print Resolution	Up to 1200 x 2400 dpi
Page Description Languages	Adobe [®] PostScript [®] 3 [™] PCL [®] 5c, 6 PDF XPS TIFF JPEG HP-GL
Color Management	Embedded spot color table, Xerox Color Corrections
Maximum Print Area	4 mm from lead edge of paper, 2 mm from side and trail edges of paper
Print Features	Application DefaultsBanner Pages Enable / DisableBi-directional Real-time StatusBooklet LayoutColor Adjustments (lightness, contrast, saturation, color balance)Color CorrectionDraft ModeFinishing (requires finishing)Fit to New Paper SizeJob Identification (Print ID or Banner, Print ID in margins on first page only or all pages)Job Monitoring (Client or Local User Interface)N-up Page Layout (up to 16 pages per sheet)Paper Selection by AttributePersonal PrintPrint Around Enable / DisablePrint from USBRun BlackSample SetSaved JobScalingSecure PrintSkip Blank PagesSpecial Pages (exception page programming: covers, inserts, exceptions pages)

Print from USB	Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port	
Operating Systems	Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® UNIX® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Xerox [®] Global Print Driver [®]	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox [®] devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox [®] Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office [®] , Ysoft [®] SafeQ [®] , Pharos [®] and others.	
MOBILE SOLUTIONS AND MOBILE	DEVICE APPS	
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone [®] or iPad [®] with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.	
Mopria® Certified	ConnectKey Technology-enabled print devices are Mopria [®] certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android [™]) smartphone, tablet and other mobile devices instantly and easily.	
Xerox [®] @printbyXerox App	@printbyXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.	
Xerox® Print Services Plug-in for Android™ (Free at Google Play™ Store)	The Xerox [®] Print Service plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.	

Xerox® Workplace Suite and Xerox® Workplace Cloud	 Xerox[®] Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience and security—for any brand printer, anywhere. Xerox[®] Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow. Xerox[®] Workplace Suite: On-site, your server Xerox[®] Workplace Cloud: Simple setup, cloud administration To learn more about the Xerox[®] Workplace Suite and Xerox[®] Workplace Cloud, visit www.xerox.com/Mobility.
SOFTWARE SOLUTIONS	
Xerox [®] ConnectKey Apps (Found at the Xerox [®] App Gallery App)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, Serverless ConnectKey Apps to the device.
SECURITY	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)
ACCOUNTING	
	NG / NETWORK ACCOUNTING (STANDARD)
Tracking	Print usage
Accounting	Xerox [®] Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.

ACCOUNTING OPTION	IS – NETWORK ACCOUNTING (ALLC	OWS CENTRAL SERVER TO MANAGE A	LL ACCOUNTING)	
	 Comprehensive manage Numerous solutions are Security enhancements Device requests accourt accounts 	ounting with up to the minute data on ho gement and enterprise scale tracking and e available through Xerox Alliance Partne s include simultaneous support for HTTP/ nt authentication from third party server of Login at control panel and pass to third p	reporting of device print usage rs. For details visit www.xerox.com 'HTTPS protocols enabling larger databases of users and	
PAPER HANDLING				
BYPASS TRAY				
Capacity ⁵	100 sheets			
Sizes		. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 2.6 x 52 in./88.9 x 98.4 mm to 320 x 132		
Weights	Simplex and Duplex: 18 I	b. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Envelopes Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Pre-Printed Postcards Recycled	
TRAY 1 AND 2				
Capacity ⁵	520 sheets each			
Sizes		7 x 17 in./100 x 148 mm to 297 x 431.8 r 6 x 18 in./100 x 148 mm to 320 x 457.2 r		
Weights	Simplex and Duplex: 18 I	b. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	
TWO TRAY MODULE				
Capacity ⁵	1,040 sheets			
Sizes	Custom sizes: 3.9 x 5.8 in	. to 12.6 x 18 in./100 x 148 mm to 320 x	457.2 mm	
Weights	Simplex and Duplex: 18 l	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	

Capacity ⁵	2,000 sheets		
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5		
Weights	Simplex and Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled
HIGH CAPACITY FEEDER			
Capacity ⁵	2,000 sheets		
Sizes	8.5 x 11 in., 7.25 x 10.5 in	n./A4, B5	
Weights	18 lb. bond to 95 lb. cove	r/64 to 216 gsm	
Types	Bond Plain Paper Cardstock Custom	Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock	Lightweight Glossy Cardstock Recycled
ENVELOPE TRAY – REPLACES TR	AY 1 (OPTIONAL)		
Capacity ⁵	Up to 50 envelopes		
Sizes	#10 commercial, Monarc Custom sizes: 3.5 x 3.85 in	h, DL, C4, C5, C6 n. to 9.5 x 13.1 in./90 x 98 mm to 241 x 3	32 mm
TOTAL CAPACITY			
VersaLink C8000/DT Capacity ⁵	1,140 sheets		
Maximum Capacity ⁵	5,140 sheets		
FINISHING			
OUTPUT TRAYS Dual Offset Catch Tray (Standard when finishers are not attached)	500 sheets (without cent 2x 250 sheets (with cent 2x 125 sheets (with cent	er tray when offset is off)	
OFFICE FINISHER (OPTIONAL)			
Capacity ⁵	750 sheets dual stapled (ets unstapled or 1,000 sheets single staple 8.5 x 11 in. / A4) (dual stapling only with ed sets of standard size paper (8.5 x 11 in	optional booklet maker)
Sizes	8.3 x 7.2 in. to 11.7 x 17 i	n./210 x 182 mm to 297 x 432 mm	
Weights	18 lb. bond to 80 lb. cove	r/60 to 220 gsm	
Multi-position Stapling	50 sheets of 24 lb. bond/	90 gsm	
Hole Punch (Optional) North America: Europe and Other Geographies:	Up to 65 lb. cover (200 gs 2/3 hole punch 2/4 hole punch	sm)	
BOOKLET MAKER FOR OFFICE F	INISHER (SCORE/CREASE,	SADDLE-STITCH STAPLE) (OPTIONAL)
Capacity ⁵	40 booklets (2 to 15 shee	ts per booklet – 20 lb./80 gsm or less)	
Sizes		EF Legal – 8.5 x 14 in./B4 SEF Ledger – 11	47. 442.000

Saddle-stitch Stapling	2 to 15 sheets/8-60 page booklet 18 lb. bond to 24 lb. bond/60 to 90 gsm	
Score / Crease	1 to 15 sheets/unstapled/60 to 105 gsm only	
OPTIONAL BR BOOKLET MAK	ER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)	
Capacity ⁵	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3	
Sizes	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling	
Weights	16 lb. bond to 110 lb. cover/60 to 300 gsm (coated and uncoated)	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb. / 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported	
Hole Punch North America Europe	2/3 hole punch 2/4 hole punch 4 hole "Swedish" punch (optional)	
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported	
DEVICE MANAGEMENT		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour [®] / AirPrint [™] Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	
REMOTE CONTROL PANEL		
	 Enables faster, more convenient technical support and user training IT administrators and other authorized users can control the device remotely from a web page on any device Remote user experience is identical to performing tasks directly at the device 	
XEROX® CENTREWARE® WE	3	
	 A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 	
XEROX® EMBEDDED WEB SER	RVER – INTEGRATED DEVICE WEB PAGE	
Device Status	 Tray status/Contents Consumables Status Billing/Usage Quick Links Online Support 	
Print Queue Viewing	Job print queue management—view and delete	
This Queue Tewing	sos principal de la contra de	
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG, TXT, PRN, TIF)	

Browsers	Microsoft [®] Internet Explorer [®] Microsoft Edge [™] Mozilla [™] Firefox [®] Apple [®] Safari [®] Google Chrome [™]		
REMOTE SERVICES			
Xerox® Automated Meter Reads (AMR)		ng meter reads for tracking and billing of Xerox® device nd-user involvement and ensures that meter reads are	
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output d manually manage supplies inventory.	levices based on actual usage, eliminating the need to	
WHAT'S IN THE BOX			
	 12,000 print capacity⁶ Drum Cartridge – One of each (Cyan, Magenta, Quick Use Guide Install Guide 	yan, Magenta, Yellow: 8,000 print capacity ⁶ , Black: Yellow, & Black: 190,000 print capacity) ⁷ Warranty Statement and Safety Regulatory Recycle	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER	
SUPPLIES			
Standard Capacity Toner Cartridges	Cyan: 7,600 standard pages ⁶ Magenta: 7,600 standard pages ⁶ Yellow: 7,600 standard pages ⁶ Black: 12,600 standard pages ⁶	106R04034 106R04035 106R04036 106R04037	
High Capacity Toner Cartridges	Cyan: 16,500 standard pages ⁶ Magenta: 16,500 standard pages ⁶ Yellow: 16,500 standard pages ⁶ Black: 20,900 standard pages ⁶	106R04046 106R04047 106R04048 106R04049	
Drum Cartridge	Cyan: 190,000 standard pages ⁷ Magenta: 190,000 standard pages ⁷ Yellow: 190,000 standard pages ⁷ Black: 190,000 standard pages ⁷	101R00602	
Waste Cartridge	47,000 standard pages ⁷	108R01504	
IBT Cleaner	160,000 standard pages ⁷	104R00256	
Transfer Roller	200,000 standard pages ⁷ 116R00015		
Office Finisher Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897	
Staple Refills for Office Finisher (3 refills per container)	15,000 staples 008R12941 (5,000 each refill) 008R12941		
Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R12964	
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R13177	

ACCESSORIES / OPTIONS	
Two Tray Module	097504969
Tandem Tray Module	097504970
High Capacity Feeder	097S04845
Envelope Tray (Replaces Tray 1)	497K17880
Office Finisher (includes Gap Filler)	497K21010
2/3 Hole Punch for Office Finisher	497K03860
2/4 Hole Punch for Office Finisher	497K03870
Booklet Maker for Office Finisher	497K03852
BR Booklet Maker Finisher with 2/3 Hole Punch (comes with Horizontal Transport)	497K21000
BR Booklet Maker finisher with 2/4 Hole Punch	097S04982
Swedish 4 Hole Punch for BR Finisher	497K14370
320 GB HDD	097S04971
Wireless Network Adapter Kit	497K16750
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)

¹ Declared print speed in accordance with ISO/IEC 24734.

¹ Declared print speed in accordance with iso/IEC 24734.
 ² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 ³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.
 ⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.
 ⁵ Paper capacities are based on 20 Ib./75 gsm stock; capacities will vary with different weight stocks.
 ⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox[®] Green World Alliance[®] collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.

